

TECHNICAL DATA SHEET

en

Name of product:

Candle Lacquer 0218

Type of product: Acrylic resin-based paint.

Application: Decorative coating for candles.

Properties: Fast-drying decorative paint.

Solids: 31 weight % 24 vol. %

Application:

Method:

Spraying

Dipping

Recommended viscosity:

10-16 sec. DIN-cup 4 mm**

10-16 sec. DIN-cup 4 mm**

Thinner:

0600-98249

0600-81035

** Please see the can label for information of recommended viscosity.

At temperatures >20°C use thinner 0600-98249.

At temperatures < 20°C use thinner 0600-81035.

STIR THE PRODUCT THOROUGHLY BEFORE AND DURING USE.

Drying:

	Drying time	Film thickness - dry
Dry to touch	4 minutes 20 °C	-

Storage: Store above 5° C.

Shelf-life: 12 Months in an unopened container

Cleaning: Tools clean with Acetone for Candle lacquer 0600-81035.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk