

TECHNICAL DATA SHEET

en

Name of product:

FAXE Kitchen Tabletop Oil 0239

Type of product: Produktet is based on pure natural oils.

Application: Used on untreated or lye treated wood on table tops and furniture etc. where you want to give the wood a beautiful golden glow with FAXE Tabletop Oil Natural or a beautiful white washed finish FAXE Tabletop Oil White.

Properties: FAXE Kitchen Tabletop Oil is developed for easy treatment, renovation and care of wooden surfaces where a water resistant and durable surface is needed.
FOOD CONTACT MATERIAL:
FAXE Kitchen Tabletop Oil complies with the legislation of Food Contact Material. Before using the kitchen tabletop it is important the oil has dried/hardened for 1 week at 20°C. Thereafter the surface can be in contact with all types of food for a shorter period and freshbread/dough for a longer period.

Solids: 86 weight % 83 vol. %

Pre-treatment:

1. Clean the wood with FAXE Intensive Cleaner.
2. When the wood is dry sanded with fine grit sandpaper grain 180.
3. Dust from grinding can be removed with a clean and damp twisted cloth.

Application:

Method:	Recommended viscosity:	Thinner:
Oil absorbing cloths	No thinning required	-

Drying:

	Drying time	Film thickness - dry
Dry to use	8 hours 20 °C	-
Fully cured	7 day(s) 20 °C	-

System Specification:

1. Apply the oil and let it soak into the wood for 15 minutes. Dry thoroughly with clean, dry cotton cloths so that no oil is left on the surface and let the wood dry for 8 hours.
2. Should the tabletop have additional high finish, sand with grain 240 followed up with a very thin layer of oil.
3. Polishing the surface with dry cotton cloth and let the wood dry for 8 hours before use.

Maintenance/Cleaning:

When needed clean with FAXE Wooden Floor Soap. After wear clean with FAXE Intensive Cleaner and retreat with FAXE Kitchen Tabletop Oil.

Storage: Store at minimum. 5°C.

Shelf-life: 24 Months in an unopened container

Cleaning: Tools clean with white spirit.

Note: Avoid dirt and moisture on the tabletop the next 7 days after applying the oil.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00 e-mail: info@efapaint.dk

www.efapaint.dk