

## TECHNICAL DATA SHEET

en

Name of product:

### Efadeck™ H2O Floor Paint 0567

<b>Type of product:</b>	Water-borne paint based on urethane- and acrylic dispersion.
<b>Application:</b>	Wooden and concrete floor coating, where a strong, dust-free surface is required.
<b>Properties:</b>	Good adhesion to wood and concrete. Can be applied on painted floors without risk of lifting.

<b>Solids:</b>	46 weight %	37 vol. %
----------------	-------------	-----------

<b>Pre-treatment:</b>	WOODEN FLOORS: The floor must be clean and free from dust, grease and soap residues. Clean with Cleaner or FAXE Intensive Cleaner. Subsequent coatings require light sanding before application. CONCRETE FLOORS: The floor must be clean and free of dust. If the floor is glazed and has an impermeable surface, sanding treatment is recommended. After this, apply Efadeck™ H2O Floor Paint twice. The first application requires 10 % thinning with water, and the second requires no thinning.
-----------------------	---

**Application:**

<b>Method:</b>	<b>Recommended viscosity:</b>	<b>Thinner:</b>
Brush and roller	No thinning required	
Water can be used to clean paint equipment and, if necessary, for thinning.		

**Drying:**

	<b>Drying time</b>	<b>Film thickness - dry</b>
Dust dry	1 hour 20 °C	30 - 50 µm
Dry to touch	4 hours 20 °C	30 - 50 µm
Dry to recoat	4 hours 20 °C	30 - 50 µm

<b>Recommended coating thickness:</b>	Wet film: 110 µm	Dry film: 40 µm
---------------------------------------	------------------	-----------------

<b>Coverage:</b>	Theoretical: 9 m <sup>2</sup> /ltr.
------------------	-------------------------------------

<b>Storage:</b>	Store above 5° C.
-----------------	-------------------

<b>Shelf-life:</b>	12 Months in an unopened container
--------------------	------------------------------------

<b>Note:</b>	This paint may replace e.g. Efadeck™ Concrete Floor Paint series 0152. If Efadeck™ H2O Floor Paint is applied on floors coated with, for example, Efadeck™ Floor Paint series 0152, they should be sanded until matt.
--------------	---

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**EFApaint A/S, Energivej 13, DK-6700 Esbjerg**

TLF. +45 75 12 86 00 e-mail: [info@efapaint.dk](mailto:info@efapaint.dk)

[www.efapaint.dk](http://www.efapaint.dk)