

## TECHNICAL DATA SHEET

en

Name of product:

### Concrete Floor Paint 0161

Type of product:	Floor paint based on urethane alkyd. Thins with white spirit.	
Application:	Cement and wooden floor coating.	
Properties:	Tough and durable floor paint that is extremely adhesive and water resistant.	
Solids:	61 weight %      48 vol. %	
Pre-treatment:	The base should be carefully cleaned to remove oil, grease, dirt and paint contaminants. Prime untreated floors with Efadeck™ Alkyd Floor Paint thinned with 20 % white spirit.	

Application:

Method:	Recommended viscosity:	Thinner:
Paint Brush	No thinning required	
White spirit can be used to clean paint equipment and, if necessary, for thinning.		

Drying:

	Drying time	Film thickness - dry
Dust dry	1 hour 20 °C	30 - 50 µm
Dry to use	3-4 hours 20 °C	30 - 50 µm
Dry to recoat	4 hours 20 °C	30 - 50 µm
Dry through	2 day(s) 20 °C	30 - 50 µm

Recommended coating thickness:	Wet film:      85 µm	Dry film:      40 µm
--------------------------------	----------------------	----------------------

Coverage:	Theoretical:      12 m²/ltr.
-----------	------------------------------

Storage:	Store cool and dry
----------	--------------------

Shelf-life:	12 Months in an unopened container
-------------	------------------------------------

Cleaning:	Tools clean with white spirit 79120.
-----------	--------------------------------------

VOC explanation:	Product marking: 2004/42/IIA(X)(YY)ZZZ EU directive number: 2004/42/ Directive annex number: IIA Product subcategory: (X) VOC content limit value g/l 2010: (YY) Maximum VOC Content in this product when ready for use, g/l: ZZZ
------------------	--

Note:	Efadeck™ H2O Floorpaint series 0567 is our water-bourne alternative.
-------	--

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**EFApaint A/S, Energivej 13, DK-6700 Esbjerg**

TLF. +45 75 12 86 00      e-mail: [info@efapaint.dk](mailto:info@efapaint.dk)

[www.efapaint.dk](http://www.efapaint.dk)