

## TECHNICAL DATA SHEET

en

Name of product:

### Efadeck™ Road Marking Paint 0182

**Type of product:** Urethane alkyd-based line paint.

**Application:** Road or asphalt marking, for example parking areas.

**Properties:** Colorfast and weather resistant paint with good coverage and abrasion resistance.

**Solids:** 67 weight % 45 vol. %

**Pre-treatment:** The base surface should be clean and free of dust.

**Application:**

**Method:**

Brush and roller

**Recommended viscosity:**

No thinning required

**Thinner:**

White spirit can be used to clean paint equipment and, if necessary, for thinning.

**Drying:**

	<b>Drying time</b>	<b>Film thickness - dry</b>
Dust dry	30 minutes 20 °C	-
Dry to touch	1 hour 20 °C	-
Dry to use	16 hours 20 °C	-

**Recommended coating thickness:** Wet film: 175 µm Dry film: 80 µm

**Coverage:** Theoretical: 5 m<sup>2</sup>/ltr.

**Storage:** Store cool and dry

**Shelf-life:** 12 Months in an unopened container

**Cleaning:** Tools clean with white spirit 79120.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**EFApaint A/S, Energivej 13, DK-6700 Esbjerg**

TLF. +45 75 12 86 00 e-mail: [info@efapaint.dk](mailto:info@efapaint.dk)

[www.efapaint.dk](http://www.efapaint.dk)