

TECHNICAL DATA SHEET

en

Name of product:

FAXE GOLak Care 0253

Type of product:	Care product based on wax emulsion, water and detergents.
Application:	On all lacquered wooden surfaces, where a durable and easy to clean surface is required.
Properties:	FAXE GOLak Care is specially developed for cleaning, care, protection and maintenance of lacquered wooden surfaces.

Pre-treatment:	<ol style="list-style-type: none">1. Shake container thoroughly before use.2. Dilute FAXE GOLak Care in warm water at a ratio of 1:30.3. Wash the wood lengthways with a mop or floor cloth.4. Dry with a well-wrung cloth or mop to remove excess solution.5. Allow to dry completely.
-----------------------	---

Drying:

	Drying time	Film thickness - dry
Dry to use	3 hours 20 °C	-

Coverage: Theoretical: 125 m²/ltr.

Storage: Store at minimum. 5°C.

Shelf-life: 24 Months in an unopened container

Note: If the wood is heavily soiled, clean first with FAXE GOLak Cleaner according to the instructions on the container.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00 e-mail: info@efapaint.dk

www.efapaint.dk