

TECHNICAL DATA SHEET**en****Name of product:****FAXE Wood Oil 0273**

Type of product:	Wood Oil based on refined vegetable oils and evt. titanwhite.
Application:	FAXE Wooden Floor Oil is for application on untreated or lye treated solid wood and parquet flooring in living areas.
Properties:	It makes the wood dirt-resistant and hard-wearing.
Solids:	59 weight % 54 vol. %
Pre-treatment:	The wood has to be sanded, clean and dry. Dirt has to be removed with FAXE Intensive Cleaner. Pre-cleansing with Faxe Intensive Cleaner improves the quality of the surface and intensifies the colour effect. Application temperature: min. 18°C. Treat large areas in sections of approx. 10-15 m ² .

Application:

Method:	Recommended viscosity:	Thinner:
White rubber squeegee	No thinning required	-
White polishing pad	No thinning required	-
Polishing Machine	No thinning required	-
Oil absorbing cloths	No thinning required	-

FAXE Wood Oil can be applied to small areas by hand or to large areas using a machine.

Drying:

	Drying time	Film thickness - dry
Resilient to careful use	5 hours 20 °C	-
Fully cured	7 day(s) 20 °C	-

System Specification:**Application:**

- Apply the oil evenly using a roller. Allow to soak in for 10 – 20 minutes, the wood should appear wet and shiny. Apply more oil, if dry areas appear.
- Skim off excess oil with the rubber squeegee. Mix the excess oil with fresh oil and use for the next section.
- consolidate and smooth the skimmed surface with the massage pad and wipe any remaining oil off with an absorbent cloth or felt pad.
- For a perfect finish, polish the surface the following day using a polishing pad and a little oil (5-10 ml/m²).
- Leave to dry for several hours and then cover areas that need to be walked on with cloths or corrugated cardboard. The floor must be protected against moisture until the oil has hardened out.

Aftercare:

Dust and loose dirt can be removed with a brush or vacuum cleaner. We recommend FAXE Wooden Floor Soap or Object Soap for cleaning. Colour and sheen can be enhanced by using FAXE Active Care. To renovate, clean the surface with FAXE Intensive Cleaner and then apply a coat of FAXE Woodcare Oil or Woodcare Paste.

Coverage:	Theoretical: 12 m ² /ltr.
Storage:	Frostfree, cool, and closed.
Shelf-life:	24 Months in an unopened container
Cleaning:	Tools clean with white spirit.

Note: If several containers containing identical product are to be used, they should be mixed together first in order to ensure a uniform result. It is always recommended to make a small test area to check surface, adhesion and colour tone.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk