

TECHNICAL DATA SHEET

en

Name of product:

FAXE Softwood Lye 0283

Type of product: Lye based on Sodium Hydroxide

Application: FAXE Softwood Lye is used on new, untreated or sanded wood on floors, walls, furniture, table tops, doors, etc.

Properties: FAXE Softwood Lye stops yellowing effectively of untreated pine- and fir. The wood will take on a light, white, but seasoned appearance, typical of surfaces treated with lye. Depending upon the type of wood, the heartwood will be accentuated.

Solids: 16 weight % 8 vol. %

Pre-treatment: The wood has to be sanded, clean and dry.
Dirt has to be removed with FAXE Intensive Cleaner.
1. The product has to be shaken/stirred before and during use.
2. The Lye is applied evenly and undiluted with a brush or a lambswoolswab at the longitudinal of the wood. Overlaps has to be removed while the wood is still wet. For an intensive effect, the treatment can be repeated after the wood is dry.
3. When the wood has dried, remove the chalk-like coating and smooth the surface of the wood using a fine sanding pad or disc.

Application:

Method:

Lyebrush

Recommended viscosity:

-

Thinner:

No thinning required

Drying:

	Drying time	Film thickness - dry
Dry to touch	5 hours 20 °C	-

System Specification:

1 x FAXE Softwood Lye

1 x Sanding

Then after-treatment with 1 of following products:

FLOORS:

FAXE Wood Oil 0273 or FAXE Prestige Oil

TABLES AND FURNITURE:

Faxe Tabletop Oil

Lightly worn areas:

FAXE Wooden Floor Soap

Coverage: Theoretical: 10 m²/litr.

Storage: Frostfree, cool, and closed.

Shelf-life: 24 Months in an unopened container

Cleaning: Tools clean with water.

Note: If several containers containing identical product are to be used, they should be mixed together first in order to ensure a uniform result. It is always recommended to make a small test area to check surface, adhesion and colour tone.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk