

## TECHNICAL DATA SHEET

en

Name of product:

### FAXE Patina Lye 0593

**Type of product:** Patina product for oak.

**Application:** FAXE Patina Lye leaves the surface as an old worn floor with a greyish look. FAXE Patina Lye can only be used on new untreated or freshly sanded wood.

**Properties:** FAXE Patina Lye will change the color of the wood through a chemical reaction and sealing treatment afterwards is therefore necessary.

**Pre-treatment:**

Manual application:  
The wood must be untreated or newly sanded. Apply FAXE Patina Lye with a brush, pad or a roller in the longitudinal direction of the wood. Apply an even layer and avoid overlapping.  
Let the surface dry for approx. 5 hours at 20° C.

Industrial application:  
Apply FAXE Patina Lye with a sponge rubber roller.  
The surface is then brushed.

**Application:**

Method:	Recommended viscosity:	Thinner:
Brush and roller	No thinning required	
Pad	No thinning required	
Industrial roller coater	No thinning required	

**Drying:**

	Drying time	Film thickness - dry
Dry to touch	5 hours 20 °C	-

**System Specification:**

After-treatment:  
To seal the wood oil-treatment with eg. FAXE Prestige Oil or Faxe High Solid Micro Oil is recommended

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

**EFApaint A/S, Energivej 13, DK-6700 Esbjerg**

TLF. +45 75 12 86 00 e-mail: [info@efapaint.dk](mailto:info@efapaint.dk)

[www.efapaint.dk](http://www.efapaint.dk)