

TECHNICAL DATA SHEET**en****Name of product:****FAXE 2K Oil 0227**

Type of product: Unique two-component oil based on vegetable oils. The oil contains a high content of wax and is formulated without the addition of organic solvents.

Application: For untreated or lye-treated parquet floors. Also very suitable for use on furniture, table tops etc.

Properties: The surface becomes dirt repellent and wear resistant. FAXE 2K Oil is also particularly resistant towards common spills like water, coffee, red wine etc. The product also tolerates cleaning with common detergents.

Solids: 100 weight % 100 vol. %

Pre-treatment: Before application, the floor should be thoroughly cleaned with FAXE Intensive Cleaner mixed with hot water (mix ratio 1:40). The wood should be completely dry afterwards before applying the oil. Drying time is between 4-8 hours at 20° C.

Application:

Method:	Recommended viscosity:	Thinner:
Polishing Machine	No thinning required	-
Putty knife	No thinning required	-
White rubber squeegee	No thinning required	-

2-Pack Products:

Catalyst	Mixing ratio (volume)	Pot life
0610-21038	4 : 1	4 hours 20 °C

Drying:

	Drying time	Film thickness - dry
Resilient to careful use	8 hours 20 °C	-
Fully cured	3 day(s) 20 °C	-

System Specification:

- The canister containing FAXE 2K Oil Part A is stirred until homogenous.
- In a mixing bucket, mix FAXE 2K Oil Part A with Part B in the mixing ratio 4:1 (volume). The mixture needs to be stirred for at least 3 minutes.
- With a flat spatula, white rubber squeegee or polishing pad, the oil is distributed on the floor.
- The surface is then polished with clean oil absorbing cloths to remove excess oil.
- The floor is ready for light traffic after approx. 8 hours at 20° C. Note that the drying time is extended at lower temperatures!

Aftercare:

The daily maintenance and cleaning of a surface treated with FAXE 2K Oil is simply vacuuming. If dirt is able to penetrate the wood surface, this can be cleaned with FAXE Wooden Floor Soap 0290, which also gives the wood a silky-smooth finish. If a thorough renovation of the floor is needed after significant wear and tear, the wood should first be cleaned with FAXE Intensive Cleaner before polishing in a new layer of FAXE 2K Oil.

Coverage: Theoretical: 45 m²/ltr.

Storage: Dry and frost free.

Shelf-life: 24 Months in an unopened container

Cleaning: Tools clean with low odour white spirit or turpentine.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk