

TECHNICAL DATA SHEET**en****Name of product:****FAXE Hardwood Lye 0284****Type of product:** Lye for treatment of hardwood surfaces like beech, oak or ash.**Properties:** Hardwood Lye gives the wood a light and bleached look. The natural structure of the wood will be retained.**Pre-treatment:** The wood has to be sanded fine, be clean and dry. Then the Hardwood Lye is applied with a metalfree brush. Any overlaps have to be removed immediately.**Application:****Method:**

Lyebrush

Recommended viscosity:

-

Thinner:

-

System Specification:

1. Hardwood Lye
2. The after-treatment should be with one of these products:
 - A. FAXE Woodoil or Prestigeoil
 - B. FAXE Floor Soap

Aftercare: Dust and loose dirt can be removed with a brush or vacuum cleaner. We recommend FAXE Active Care or FAXE Wooden Floor Soap for cleaning. To renovate, clean the surface with FAXE Intensive Cleaner and then apply a coat of FAXE Woodcare Oil or FAXE Floor Soap.

Coverage: Theoretical: 10 m²/ltr.**Storage:** Frostfree, cool, and closed.**Shelf-life:** 12 Months in an unopened container**Cleaning:** Tools clean with water.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg**TLF. +45 75 12 86 00****e-mail: info@efapaint.dk****www.efapaint.dk**