

TECHNICAL DATA SHEET**en****Name of product:****FAXE Special Lye 0288****Type of product:** Lye based on Sodium hydroxide.**Application:** FAXE Special Lye is used mainly on untreated or freshly sanded floorings, where a special surface is wanted. For oak, where a smoked or coloured tone is wanted or on softwood where the natural look is wanted.**Properties:** FAXE Special Lye stops untreated pine, spruce and pitch pine from yellowing and creates a change in colour typical for seasoned wood. Depending upon the type of wood, the heartwood will be accentuated, structure and grain will remain. Gives a smoked effect e.g. on oak.**Solids:** 3 weight % 3 vol. %**Pre-treatment:** The wood must be sanded down, with a fine grain pad or disc, clean and dry. Remove stubborn dirt using Faxe Intensive Cleaner.**Application:****Method:**Nylon brush
lye applicator**Recommended viscosity:**No thinning required
No thinning required**Thinner:**

NB! When applied with rollers a special edition with higher viscosity of the product should be used.

Drying:

	Drying time	Film thickness - dry
Dry to use	5 hours 20 °C	.

System Specification:

Application:

1. Apply the undiluted lye evenly, with the grain, using a nylon brush or lambswool lye applicator. Smooth out overlaps, as long as the wood is still wet.
2. For a particularly intensive effect, repeat the process after the first coat has dried.
3. When the wood has dried, remove the chalk-like coating and smooth the surface of the wood using a fine sanding pad or disc.

After Care:

The finish should be applied in to suit the planned usage: FAXE Wooden Floor Oil, FAXE Prestige Oil for particularly high-quality wooden floors, FAXE Wooden Floor Soap for robust and natural Scandinavian style soft wood floors and FAXE Tabletop Oil for table tops and worktops.

Aftercare: Dust and loose dirt can be removed with a brush or vacuum cleaner. We recommend FAXE Active Care or FAXE Wooden Floor Soap for cleaning. To renovate, clean the surface with FAXE Intensive Cleaner and then apply a coat of FAXE Woodcare Oil or FAXE Floor Soap.

Coverage: Theoretical: 10 m²/ltr.**Storage:** Frostfree, cool, and closed.**Shelf-life:** 12 Months in an unopened container**Cleaning:** The tools should be cleaned with water.**Available colors:** FAXE Special Lye is not pigmented. In order to apply colour at the same time, add up to 10% FAXE Combicolor.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk