

TECHNICAL DATA SHEET

en

Name of product:

Arsinol™ 172 Wood Care Oil Natur

Type of product: Alkyd-based wood preservative.
Application: Oil for exterior use. This product has been developed for exterior use.
Properties: Arsinol™ 172 Wood Care Oil provides protection and prevent the wood from drying out.

Solids: 15 weight % 12 vol. %

Pre-treatment: Clean dirty woodwork with a stiff brush. The wood should be clean and dry before further painting. (Max. moisture content 10-15 %).

Application:

Method:	Recommended viscosity:	Thinner:
Paint Brush	No thinning required	

Drying:

	Drying time	Film thickness - dry
Dust dry	6-8 hours 20 °C	-
Dry to touch	24 hours 20 °C	-

Coverage: Theoretical: 10 m²/ltr.

Storage: Store cool and dry

Shelf-life: 24 Months in an unopened container

Cleaning: Tools clean with white spirit 79120.

VOC explanation: Product marking: 2004/42/IIA(X)(YY)ZZZ EU directive number: 2004/42/
Directive annex number: IIA
Product subcategory: (X)
VOC content limit value g/l 2010: (YY)
Maximum VOC Content in this product when ready for use, g/l: ZZZ

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00 e-mail: info@efapaint.dk

www.efapaint.dk