
TECHNICAL DATA SHEET

en**Name of product:****FAXE Decking Cleaner Conc. 0580 99300**

Type of product: Water-borne concentrated cleaning agent.**Application:** Depth cleaning of wooden decking and tiles. FAXE Decking Cleaner Conc. is suitable for cleaning of patio coverings made of untreated or oiled wood, stone or composite material.**Properties:** FAXE Decking Cleaner Conc. removes dirt and coatings. When using a scrubber with stiff bristles the cleaning is very quick and efficiently, also for profiled surfaces.

Application:

Method:	Recommended viscosity:	Thinner:
Brush	-	water
Scrub	-	water

* The temperature must be above 10°C.

* Make the terrace wet.

* Scrub the surface with FAXE Decking Cleaner Conc. thinned with water. 1 part of Decking Cleaner to 5 parts of water.

* Rinse off loosened dirt and growths with plenty of water.

* Leave the terrace to dry.

The finished result depends, amongst other things, on the preparatory treatment, structure and natural colour of the substrate. For this reason, try out first on a sample area.

System Specification:**AFTER CARE:**

Tiles:

As aftercare FAXE Patio Sealer can be used. FAXE Patio Sealer will prolong the effect of the treatment.

Wooden deckings:

Finally FAXE Decking Oil or Arsinol Transparent is used. If the wood is very weathered or faded and need refreshing the FAXE Decking Oil or Arsinol Transparent in a similar colour is recommended.

Storage: Store above 10° C.**Shelf-life:** 12 Months in an unopened container**Cleaning:** The tools should be cleaned with water.

Note: FAXE Decking Cleaner Conc. does not damage the adjacent vegetation.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dkwww.efapaint.dk