

TECHNICAL DATA SHEET**en****Name of product:****FAXE Active Care 0280 07300 - 07301**

Type of product: FAXE Active Care is a cleaning and wood care agent for oiled and other open pored, treated surfaces. Active Care contains mild, surfactants (surface-active agents) and nurturing wax.

Application: It is suitable for use on natural, oiled wooden floors.

Properties: Active Care dries to give silk mat or mat look. It forms a water-repellent and easy to clean protective surface.

Solids: 17 weight % 17 vol. %

Pre-treatment: Use a vacuum cleaner to remove loose dirt before starting treatment. Before the first application, remove any old conditioner and stubborn dirt using Faxe Intensive Cleaner. If the surface is in poor condition, first apply a coat of oil and allow this to dry. Do not clean newly oiled surfaces for the first 7 days after application.

Application:**Method:**

-

Recommended viscosity:

-

Thinner:

-

First application: Lambswool applicator

Cleaning: mop, bucket

Drying:

	Drying time	Film thickness - dry
Dry to use	1 hour 20 °C	-

System Specification:

If the wood has become dirty during installation, it should firstly be cleaned with [FAXE Intensive Cleaner](#).

- Shake the can.
- The wood must be clean, dry and dust-free.
- Dissolve FAXE Active Care in tempered water in the ratio of 1:10 – 1:20.
- Wash the floor in the direction of the wood grain using a wrung-out mop or cloth.
- Allow the surface to dry in 30-60 min. before using the floor

NOTE! On dark wood as for example Merbau or Jatoba, you achieve a more beautiful depth and tone by using a stronger dilution of [FAXE Oil Soap](#) instead of FAXE Active Care.

Coverage: Theoretical: 75-200 m²/ltr.

Storage: Frostfree, cool, and closed.

Shelf-life: 12 Months in an unopened container

Cleaning: The tools should be cleaned with water.

Note: Pour the content in a bucket and stir well during use. If several containers containing identical product are to be used, they should be mixed together first in order to ensure a uniform result. It is always recommended to make a small test area to check surface, adhesion and colour tone.

This information is based on our present state of knowledge and is intended to provide general notes on our products and their use. It should not, therefore, be construed as guaranteeing specific properties of the product described or its suitability for a particular application. The quality of our products is guaranteed under our General Conditions of Sale.

EFApaint A/S, Energivej 13, DK-6700 Esbjerg

TLF. +45 75 12 86 00

e-mail: info@efapaint.dk

www.efapaint.dk